



# CD-12L Portable Dehumidifier.

The Portable Dehumidifier comes with a Soft Key Control Panel that allows you to choose your desired humidity level and extraction rate. You can also choose to delay the start-up or switch off with a programmable timer. With the help of internal diagnostic, the "Liquid Crystal Display" allows you to view the humidity and temperature readings along with your other settings. Precise and efficient, the is ideal for the detailed.



CD-12L

### Power Consumption

190 Watts

### Voltage

220V-240V/50 Hz

### Extraction (30°C, 80% RH)

12 Liters / day

### Humidity Setting

Available

### Running Temperature

5 - 35°C

### Rated Current

0.9A

### Coolant

R134A

### Noise Level (approx.)

>44 db

### Weight

9.7 kg

### Dimension (W x D x H) mm

325 x 248 x 475

### Tank Capacity

2.5 liters

### Air Volume

100 CMH

### Control Technologies FZE

T : +971 6 5489626

M: +971 50 1537113

F : +971 6 5489627

E : sales@ctrltechnologies.com

w : www.ctrltechnologies.com





# CD-12L Portable Dehumidifier.



CD-12L



## Control Technologies FZE

T : +971 6 5489626

M: +971 50 1537113

F : +971 6 5489627

E : sales@ctrltechnologies.com

w : www.ctrltechnologies.com

